

## APPENDIX A The Saffir-Simpson Hurricane Scale

(From: TPC/National Hurricane Center - <http://www.nhc.noaa.gov/aboutsshs.html>)

The Saffir-Simpson Hurricane Scale is a 1-5 rating based on the hurricane's present intensity. This is used to give an estimate of the potential property damage and flooding expected along the coast from a hurricane landfall. Wind speed is the determining factor in the scale, as storm surge values are highly dependent on the slope of the continental shelf in the landfall region. Note that all winds are using the U.S. 1-minute average.

### Category One Hurricane:

Winds 74-95 mph (64-82 kt or 119-153 km/hr). Storm surge generally 4-5 ft above normal. No real damage to building structures. Damage primarily to unanchored mobile homes, shrubbery, and trees. Some damage to poorly constructed signs. Also, some coastal road flooding and minor pier damage. Hurricanes [Allison](#) of 1995 and [Danny](#) of 1997 were Category One hurricanes at peak intensity.

### Category Two Hurricane:

Winds 96-110 mph (83-95 kt or 154-177 km/hr). Storm surge generally 6-8 feet above normal. Some roofing material, door, and window damage of buildings. Considerable damage to shrubbery and trees with some trees blown down. Considerable damage to mobile homes, poorly constructed signs, and piers. Coastal and low-lying escape routes flood 2-4 hours before arrival of the hurricane center. Small craft in unprotected anchorages break moorings. [Hurricane Bonnie](#) of 1998 was a Category Two hurricane when it hit the North Carolina coast, while [Hurricane Georges](#) of 1998 was a Category Two Hurricane when it hit the Florida Keys and the Mississippi Gulf Coast.

### Category Three Hurricane:

Winds 111-130 mph (96-113 kt or 178-209 km/hr). Storm surge generally 9-12 ft above normal. Some structural damage to small residences and utility buildings with a minor amount of curtain wall failures. Damage to shrubbery and trees with foliage blown off trees and large trees blown down. Mobile homes and poorly constructed signs are destroyed. Low-lying escape routes are cut by rising water 3-5 hours before arrival of the hurricane center. Flooding near the coast destroys smaller structures with larger structures damaged by

## **RI Statewide Hazard Risk and Vulnerability Assessment**

battering of floating debris. Terrain continuously lower than 5 ft above mean sea level may be flooded inland 8 miles (13 km) or more. Evacuation of low-lying residences with several blocks of the shoreline may be required. Hurricanes [Roxanne](#) of 1995 and [Fran](#) of 1996 were Category Three hurricanes at landfall on the Yucatan Peninsula of Mexico and in North Carolina, respectively.

### **Category Four Hurricane:**

Winds 131-155 mph (114-135 kt or 210-249 km/hr). Storm surge generally 13-18 ft above normal. More extensive curtain wall failures with some complete roof structure failures on small residences. Shrubs, trees, and all signs are blown down. Complete destruction of mobile homes. Extensive damage to doors and windows. Low-lying escape routes may be cut by rising water 3-5 hours before arrival of the hurricane center. Major damage to lower floors of structures near the shore. Terrain lower than 10 ft above sea level may be flooded requiring massive evacuation of residential areas as far inland as 6 miles (10 km). [Hurricane Luis](#) of 1995 was a Category Four hurricane while moving over the Leeward Islands. Hurricanes [Felix](#) and [Opal](#) of 1995 also reached Category Four status at peak intensity.

### **Category Five Hurricane:**

Winds greater than 155 mph (135 kt or 249 km/hr). Storm surge generally greater than 18 ft above normal. Complete roof failure on many residences and industrial buildings. Some complete building failures with small utility buildings blown over or away. All shrubs, trees, and signs blown down. Complete destruction of mobile homes. Severe and extensive window and door damage. Low-lying escape routes are cut by rising water 3-5 hours before arrival of the hurricane center. Major damage to lower floors of all structures located less than 15 ft above sea level and within 500 yards of the shoreline. Massive evacuation of residential areas on low ground within 5-10 miles (8-16 km) of the shoreline may be required. [Hurricane Mitch](#) of 1998 was a Category Five hurricane at peak intensity over the western Caribbean. [Hurricane Gilbert](#) of 1988 was a Category Five hurricane at peak intensity and is the strongest Atlantic tropical cyclone of record.

## RI Statewide Hazard Risk and Vulnerability Assessment

### APPENDIX B: The Fujita Scale

(From the Tornado Project - <http://www.tornadoproject.com/fscale/fscale.htm#fscale> table)

F-Scale Number	Intensity Phrase	Wind Speed	Type of Damage Done
F0	Gale tornado	40-72 mph	Some damage to chimneys; breaks branches off trees; pushes over shallow-rooted trees; damages sign boards.
F1	Moderate tornado	73-112 mph	The lower limit is the beginning of hurricane wind speed; peels surface off roofs; mobile homes pushed off foundations or overturned; moving autos pushed off the roads; attached garages may be destroyed.
F2	Significant tornado	113-157 mph	Considerable damage. Roofs torn off frame houses; mobile homes demolished; boxcars pushed over; large trees snapped or uprooted; light object missiles generated.
F3	Severe tornado	158-206 mph	Roof and some walls torn off well constructed houses; trains overturned; most trees in fores uprooted
F4	Devastating tornado	207-260 mph	Well-constructed houses leveled; structures with weak foundations blown off some distance; cars thrown and large missiles generated.
F5	Incredible tornado	261-318 mph	Strong frame houses lifted off foundations and carried considerable distances to disintegrate; automobile sized missiles fly through the air in excess of 100 meters; trees debarked; steel reinforced concrete structures badly damaged.
F6	Inconceivable tornado	319-379 mph	These winds are very unlikely. The small area of damage they might produce would probably not be recognizable along with the mess produced by F4 and F5 wind that would surround the F6 winds. Missiles, such as cars and refrigerators would do serious secondary damage that could not be directly identified as F6 damage. If this level is ever achieved, evidence for it might only be found in some manner of ground swirl pattern, for it may never be identifiable through engineering studies

5. Relative Environmental Exposure Map

#### **IV. Combined Scores by Census Tract**

1. Hazard Scores Multiplied by Combined Exposure Scores
  - a. Flood Exposure Scores
  - b. Earthquake Exposure Scores
  - c. Hail Exposure Scores
  - d. Hurricane Exposure Scores
  - e. Snow Exposure Scores
  - f. Combined Exposure Scores
  
2. Exposure Scores Multiplied by Combined Hazard Scores
  - a. Critical Facilities Hazard Scores
  - b. Social Hazard Scores
  - c. Economic Hazard Scores
  - d. Environmental Hazard Scores

#### **V. Detailed Hazard/Exposure Combinations by Census Tract**

1. Schools at Earthquake Risk
2. Elderly Population at Snow Risk

## **APPENDIX C: Hazard, Exposure, and Combined Score Maps**

### **I. Hazard Scores by Census Tract**

1. Relative Hazard Map Comparison
2. Relative Flood Hazard Map
3. Relative Hail Hazard Map
4. Relative Hurricane Hazard Map
5. Relative Earthquake Hazard Map
6. Relative Snow Hazard Map
7. Relative Temperature Extreme Hazard Map
8. Relative Combined Hazard Map

### **II. Exposure Scores by Census Tract**

1. Combined Relative Exposure Maps
2. Relative Critical Facilities Exposure Map
3. Relative Social Exposure Map
4. Relative Economic Exposure Map
5. Relative Environmental Exposure Map
6. Relative Combined Exposure Map

### **III. Exposure and Hazard Scores by Community**

1. Combined Relative Exposure Maps
2. Relative Critical Facilities Exposure Map
3. Relative Social Exposure Map
4. Relative Economic Exposure Map